



1056-ES MASK OFF

SPECIALTIES FOR MAINTENANCE AND SANITATION SINCE 1947

EASILY AND COMPLETELY REMOVES OLD COATINGS OF FM 1055-ES OUTDOOR MASK-A-WAY AND ACCUMULATED OVERSPRAY.



Removing Outdoor Mask-A-Way is Easy — Just Spray On Mask Off and Pressure Wash Off.

Your lift equipment was protected from overspray with FM 1055-ES Outdoor Mask-A-Way, now remove all that build-up with FM 1056-ES Mask Off and start over again with fresh, clean equipment.

CONVENIENT, ready-to-use formula—no messy, time-consuming mixing to do, no confusing dilution ratios to remember. Just apply the Mask Off straight.

FAST — Within 30 minutes, the FM 1056-ES has softened the Outdoor Mask-A-Way to where it can be easily washed off the surface with a hot water pressure rinse.

EFFECTIVE — Mask Off removes the coating through chemical action alone. No scrubbing or brushing is necessary.

SAFE TO USE and environmentally friendly. When used as directed, FM 1056-ES poses no hazards to users and can be disposed of down storm drains and sewers during the pressure washer rinsing of the equipment.

Packed in 55 Gallon Drums

Rev. 11-20-14

Toll Free: 800-238-5150
Local: 901-363-4340
Fax: 901-375-3600

Delta Foremost Chemical Corp.
3915 AIR PARK ST. • P.O. BOX 30310 • MEMPHIS, TENNESSEE 38130-310

Visit our Web Site at:
www.deltaforemost.com



TECHNICAL DATA

FOREMOST 1056-ES MASK OFF

Rev. 3-19-98

DESCRIPTION: FM 1056-ES Mask Off is a cleansing product used to remove 1055-ES Outdoor Mask-A-Way and other similar masking products along with paint and solvent overspray.

APPLICATION: For best results, it is recommended that FM 1056-ES Mask Off not be applied to hot surfaces. Do not apply to machinery that has been exposed to direct sunlight in the heat of the summer. If it is not possible to shade the machinery, it is recommended that the removal process be performed in the morning or late afternoon. FM 1056-ES Mask Off should be used without dilution.

- DIRECTIONS:**
1. Apply undiluted FM 1056-ES Mask Off to all surfaces that have been coated with FM 1055-ES Outdoor Mask-A-Way using a pump-up sprayer or other suitable application device.
 2. Allow up to 30 minutes contact time for the FM 1056-ES Mask Off to soften and loosen the Outdoor Mask-A-Way from the surface.
 3. Use a hot water pressure washer to remove all paint overspray and Mask-A-Way from the machinery.
 4. Reapply FM 1055-ES Outdoor Mask-A-Way to machinery before returning it to the field.

PRECAUTIONS: Alkaline cleaning compound. May be harmful if swallowed. Do not mix with foodstuffs. Causes irritation to eyes and skin. Avoid contact with eyes and skin.

FIRST AID: EYES: In case of contact, immediately flush with plenty of water for at least 15 minutes. Get medical attention immediately. **SKIN:** Wash with soap and water. Wash clothing before reuse. **INGESTION:** If swallowed, do not induce vomiting. If person is conscious, give large amounts of water or milk if available. Get medical attention immediately. Keep this and all similar products out of the reach of children.