



1195 PAINT AND RUST REMOVER

SPECIALTIES FOR MAINTENANCE AND SANITATION SINCE 1947



If you are using a hot vat and getting only grease, soil and paint removal, why not use Foremost 1195 PAINT AND RUST REMOVER and at the same time accomplish rust, corrosion and water scale removal.

This uniquely chelate alkaline product does away with the need of multiple vats. Requires only one simple mild steel vat. Eliminates the use of hazardous acids and expensive glass or rubber lined tanks to contain them.

NON-CORROSIVE—Ferrous metals may be submerged in Delta's Foremost 1195 Paint and Rust Remover without danger of metal loss or embrittlement. No corrosive fumes to rust nearby metal.

FAST—Complete cleaning. External grease-bonded soils and corrosion, plus internal water scale and rust are literally dissolved in a few hours.

PROTECTS—For ordinary shop use. No unpleasant or toxic fumes. Simply avoid skin contact as you would any alkaline solution.

ECONOMICAL—No special tanks or equipment needed. Foremost 1195 Paint and Rust Remover is sold in concentrated, anhydrous form that dissolves readily in water. Solutions are long-lived.

Packed In 500 lb. Drums

REMOVES...

- **RUST!**
- **PAINT!**
- **GREASE!**
- **WATER SCALE!**
- **CARBON!**
- **CORROSION!**

**AT THE SAME TIME
WITH ONE SOLUTION!**

FOREMOST 1195 Paint and Rust Remover is the answer to all these cleaning problems—

**POWER MACHINERY
AIR CONDITIONING COMPRESSORS**
Stationary Engines • Motors

**OIL FIELDS
HEAT TRANSFER REFINERIES**
Valves • Fittings • Pipe Couplings

MEAT PACKERS
Hooks • Trolleys

INDUSTRIAL
Reject Stripping Equipment Parts

**A DYNAMIC NEW DEVELOPMENT BY
DELTA FOREMOST CHEMICAL'S
CREATIVE LABORATORIES**

Authorized by USDA for use in
federally inspected meat and poultry plants.

Rev. 9-8-14

Toll Free: 800-238-5150
Local: 901-363-4340
Fax: 901-375-3600

Delta Foremost Chemical Corp.
3915 AIR PARK ST. • P.O. BOX 30310 • MEMPHIS, TENNESSEE 38130-310

Visit our Web Site at:
www.deltaforemost.com



TECHNICAL DATA

FOREMOST 1195 PAINT & RUST REMOVER

Rev. 10-14-11

DESCRIPTION: A unique blend of powdered alkaline ingredients possessing the ability to remove paint, lime scale, rust, oil and other types of ordinary contamination from ferrous metals.

APPLICATION: Recommended for use in hot soaker vat operations for paint stripping and rust and lime scale removal. Foremost 1195 is used in industrial washing machines for removing flash rust and deposits of dirt and oil. Foremost 1195 Compound is highly useful where flash rust and grease must be kept off pans, kettles, racks and meat hooks. In small parts manufacture, Foremost 1195 is effective in removing rust and oil from parts accumulated in storage.

DIRECTIONS: **FOR HOT VAT CLEANING:** Use 8 to 16 ounces per gallon of water. Maintain the temperature at 180°F to 200°F.

FOR HOT VAT PAINT STRIPPING AND FOR SCALE AND HEAVY RUST REMOVAL: Use 1 to 3 pounds per gallon of water, maintaining temperature as close to boiling as possible.

FOR JET WASHERS: Use 4 ounces to 10 ounces per gallon of water. Best results are obtained at concentrations of 8 to 10 ounces per gallon of water, maintaining temperature of 180°F to 190°F.

NOTE: Do not use on wood, painted surfaces, aluminum or other soft, non-ferrous metals.

PRECAUTIONS: **KEEP OUT OF REACH OF CHILDREN.** Contains sodium hydroxide. Causes severe burns to skin and eyes. Do not get in eyes, on skin, or clothing. Do not take internally. Avoid breathing dust. Keep container closed. Use with adequate ventilation. Wash thoroughly after handling. While making solution, add compound slowly to surface to avoid boiling or violent splattering. When handling, always wear chemical splash goggles, face shield, rubber gloves and protective clothing.

FIRST AID: EYES AND SKIN: In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. Remove contaminated clothing and footwear. Wash clothing before reuse. Destroy contaminated footwear. **INGESTION:** If swallowed, do not induce vomiting. If person is conscious, give large quantities of water or milk, if available. Get medical attention immediately.

Before using this product, read the Material Safety Data Sheet (MSDS) for more detailed information regarding safe handling.

FACTS

1. Non-corrosive to ferrous metals
2. Fast action
3. Safe for ordinary shop use
4. No special equipment required
5. Long-lived solutions when properly employed

BENEFITS

1. Metal is not embrittled or eaten away
2. No corrosive fumes to rust nearby metal
3. Complete cleaning of internal rust and water scale as well as external grease bonded soils and surface rust
4. Concentrated, anhydrous form dissolves readily in water
5. Adds rust and scale removal ability to other vat compounds