



1812C-ES
Citri-Zip
ASPHALT & TAR REMOVER

SPECIALTIES FOR MAINTENANCE AND SANITATION SINCE 1947

FASTER CLEAN-UP OF ASPHALT AND TAR



Before Citri-Zip



After . . . asphalt is easily rinsed away.

CITRI-ZIP AWAY LABOR COSTS!

WATER EMULSIFIABLE for fast, safe, thorough removal of asphalt, tar or any bituminous build-up.

EASY-FAST—Spray or swab Foremost 1812C-ES on contaminated surfaces. Foremost 1812C-ES's unparalleled solvent action takes place in minutes; then simply flush with water pressure or steam. Unique wetting and emulsification properties give film-free drying.

PROTECTS—Foremost 1812C-ES is non-caustic and non-corrosive. It may be used on ferrous or non-ferrous metals, including aluminum.

ECONOMICAL—Highly active, this light viscosity liquid gives economical coverage. Speed of cleaning offers additional savings in both time and labor. 10 to 15 times more effective than petroleum distillates. Also recommended for difficult degreasing such as 5th wheels and removing Cosmoline and other protective compounds.

ENTHUSIASTICALLY RECOMMENDED FOR tar and asphalt removal from storage and application trucks, tank wagons, paving and roofing equipment, etc. Cleans spillages from concrete, stone, brick, tile and other masonry surfaces.

**CONTAINS NO CFC'S OR OTHER
OZONE DEPLETING SUBSTANCES**

NO PETROLEUM DISTILLATES

NO VOC'S

NO HAP'S

A NATURAL SOLVENT

Packed in 55 Gallon Drums

Rev. 3-5-14

Toll Free: 800-238-5150
Local: 901-363-4340
Fax: 901-375-3600

Delta Foremost Chemical Corp.
3915 AIR PARK ST. • P.O. BOX 30310 • MEMPHIS, TENNESSEE 38130-310

Visit our Web Site at:
www.deltaforemost.com



TECHNICAL DATA

FOREMOST 1812C-ES CITRI-ZIP ASPHALT AND TAR REMOVER

Rev. 03-17-99

DESCRIPTION: A heavy duty natural solvent designed for efficient removal of roofing tar, asphalt, oil, grease and road tar which will rinse freely from all surfaces when flushed with water. It is also an excellent grease solvent for regular maintenance work around industrial equipment.

APPLICATION: This product is recommended for use on road primer tanks, auxiliary tanks, transport trucks, earth moving equipment, railroad equipment and industrial equipment for ordinary tar and asphalt removal. It is also successfully used for removal of roofing tar and asphalt from concrete, stone, brick, tile, and other masonry surfaces. It is NOT recommended for automotive finishes.

DIRECTIONS: To remove roofing tar spillage and stains from masonry surfaces, apply with long handle brushes or mops, allow to set, and flush with water. For stubborn deposits, scraping may be required to assist the solvent action.

For cleaning surfaces of machinery, industrial equipment, trucks, etc., application can be made by spraying, brushing, or wiping the undiluted concentrate over the surface involved, and either wipe or flush with water. Procedures for cleaning may be altered to meet specific needs and can usually be best determined by the user. If more detailed instructions are required please advise. For best results, application should be made before deposits become hardened.

PRECAUTIONS: Do not take internally. May cause eye irritation. Avoid contact with eyes.

FIRST AID: In case of contact, immediately flush eyes with large amounts of water until burning ceases. Get medical attention immediately if irritation persists. Before using this product, read the Material Safety Data Sheet (MSDS) for more detailed information regarding safe handling.

FACTS

BENEFITS

- | | |
|-----------------|--|
| 1. Fast | 1. Unique solvent activity takes only minutes to dissolve bituminous buildup |
| 2. Water rinses | 2. Wetting and emulsifying properties give film-free drying after the water rinse |
| 3. Efficient | 3. Removes tar and asphalt 10 to 15 times more effectively than ordinary petroleum distillates |
| 4. Protects | 4. Noncaustic, noncorrosive. Harmless to aluminum and other metals. |