



527 PARTS CLEANER

SPECIALTIES FOR MAINTENANCE AND SANITATION SINCE 1947

The Efficient, Time-Saving Parts Cleaning Solvent For Use In Most Modern Parts Washers



- **REDUCES REPAIR TIME & LABOR**
- **SAFE ON ALL METALS**
- **NO OFFENSIVE FUMES OR ODORS**
- **ECONOMICAL**

HI-SPEED removal of grime, grease, oil and dirt. Energized, highly active hydrocarbon solvents clean parts fast and with less brushing.

LONG-LIVED cleaning power keeps it operating at peak performance over and over again for economical operation.

NOTE: Excellent for use in Transmission Torque Converter Cleaning Machines.

FOREMOST 527 PARTS CLEANER is ideally suited for many cleaning operations—

AUTOMOTIVE

- Parts Rebuilders
- Repair Shops
- Dealer Service Bays
- Fleet Garages
- Machine Shops
- Motor Pools

INDUSTRIAL

- Maintenance Departments
- Production Cleaning
- Die Maintenance
- Tool Clean-Up

SPECIALTY

- Small Engine Repair
- Motorcycle Shops
- Equipment Rental Shops
- Typewriter Rebuilders
- Office Machine Dealers

Packed in 55 Gallon Drums

Rev. 7-23-14

Toll Free: 800-238-5150
Local: 901-363-4340
Fax: 901-375-3600

Delta Foremost Chemical Corp.

3915 AIR PARK ST. • P.O. BOX 30310 • MEMPHIS, TENNESSEE 38130-310

Visit our Web Site at:
www.deltaforemost.com



TECHNICAL DATA

FOREMOST 527 PARTS CLEANER

Rev. 7-23-14

DESCRIPTION: A unique oil and grease solvent in ready-to-use form for convenient use. It is blended to give high performance cleaning with long solution life. It will penetrate and dissolve grease, oil, grime and grease bonded dirt from metals and other surfaces. Foremost 527 Parts Cleaner is a neutral cleaner that is non-toxic, non-injurious to good paint, safe on metals and free of objectionable odor.

APPLICATION: Foremost 527 Parts Cleaner is highly recommended for cleaning automotive engines, chassis, industrial machinery, farm and road equipment. It is widely used in automotive, diesel, electrical and industrial maintenance shops. Foremost 527 Parts Cleaner is excellent for use in transmission torque convertor cleaning machines.

DIRECTIONS:

1. Add Foremost 527 to solution tank to desired level.
2. Soak parts for 5 to 30 minutes with or without agitation, or . . .
3. Wash parts in a recirculating washer with light brushing action.
4. Blow contamination off parts with air or simply let dry.

PRECAUTIONS: **KEEP OUT OF REACH OF CHILDREN.** May be harmful if swallowed. Contains aromatic and aliphatic hydrocarbons. Combustible liquid. Keep away from heat and open flame. Use with adequate ventilation. Do not take internally.

FIRST AID: EYES: Flush with large amounts of water for at least 15 minutes and see physician.

SKIN: In case of contact, wash with soap or mild detergent and water. **INGESTION:** Get immediate medical attention. **INHALATION:** If breathing difficulties, dizziness, or lightheadness occurs, remove to fresh air.

Before using this product, read the Material Safety Data Sheet (MSDS) for more detailed information regarding safe handling.