



722-ES ZIP TAR REMOVER

SPECIALTIES FOR MAINTENANCE AND SANITATION SINCE 1947

FASTER CLEAN-UP OF ASPHALT AND TAR



Before



After - Tar Is Easily Rinsed Away

ZIP AWAY TIME COSTS!

WATER EMULSIFIABLE for fast, safe, thorough removal of asphalt, tar or any bituminous build-up.

EASY-FAST—Spray or swab Foremost 722-ES on contaminated surfaces. Foremost 722-ES's unparalleled solvent action takes place in minutes; then simply flush with water pressure or steam. Unique wetting and emulsification properties give film-free drying.

PROTECTS—Foremost 722-ES is non-caustic and non-corrosive. It may be used on ferrous or non-ferrous metals, including aluminum.

CONTAINS NO CFC'S OR OTHER OZONE DEPLETING SUBSTANCES

ECONOMICAL—Highly active, this light viscosity liquid gives economical coverage. Speed of cleaning offers additional savings in both time and labor. 10 to 15 times more effective than petroleum distillates. Also recommended for difficult degreasing such as 5th wheels and removing Cosmoline and other protective compounds.

ENTHUSIASTICALLY RECOMMENDED FOR tar and asphalt removal from storage and application trucks, tank wagons, paving and roofing equipment, etc. Cleans spillages from concrete, stone, brick, tile and other masonry surfaces.

Packed in 55 Gallon Drums

Rev. 7-3-13

Toll Free: 800-238-5150
Local: 901-363-4340
Fax: 901-375-3600

Delta Foremost Chemical Corp.
3915 AIR PARK ST. • P.O. BOX 30310 • MEMPHIS, TN 38130-0310

Visit our Web Site at:
www.deltaforemost.com



TECHNICAL DATA

FOREMOST 722-ES ZIP TAR REMOVER

Rev. 7-3-13

DESCRIPTION: A heavy duty solvent designed for efficient removal of roofing tar, asphalt, oil, grease and road tar which will rinse freely from all surfaces when flushed with water. It is also an excellent grease solvent for regular maintenance work around industrial equipment.

APPLICATION: This product is recommended for use on road primer tanks, auxiliary tanks, transport trucks, earth moving equipment, railroad equipment and industrial equipment for ordinary tar and asphalt removal. It is also successfully used for removal of roofing tar and asphalt from concrete, stone, brick, tile, and other masonry surfaces. It is NOT recommended for automotive finishes.

DIRECTIONS: To remove roofing tar spillage and stains from masonry surfaces, apply with long handle brushes or mops, allow to sit, and flush with water. For stubborn deposits, scraping may be required to assist the solvent action.

For cleaning surfaces of machinery, industrial equipment, trucks, etc., application can be made by spraying, brushing, or wiping the undiluted concentrate over the surface involved, and either wipe or flush with water. Procedures for cleaning may be altered to meet specific needs and can usually be best determined by the user. If more detailed instructions are required please advise. For best results, application should be made before deposits become hardened.

PRECAUTIONS: **KEEP OUT OF REACH OF CHILDREN.** Flammable liquid and vapor. Do not take internally. **MAY BE HARMFUL IF SWALLOWED.** If ingested, get immediate medical attention. Keep away from heat and open flame. Use with adequate ventilation. Avoid contact with skin and eyes. Keep container closed when not in use. Contact with skin can cause moderate irritation, defatting, dermatitis.

FIRST AID: **If on SKIN:** Wash thoroughly with soap or mild detergent and water. **If in EYES:** Flush with large amounts of water, lifting upper and lower lids occasionally. Get medical attention. **INGESTION:** Get immediate medical attention. **If INHALED:** If affected, remove individual to fresh air. If breathing is difficult, administer oxygen. Keep person warm, quiet, and get medical attention.

Before using this product, read the Material Safety Data Sheet (MSDS) for more detailed information regarding safe handling.

FACTS

1. Fast
2. Water rinses
3. Efficient
4. Protects

BENEFITS

1. Unique solvent activity takes only minutes to dissolve bituminous build-up
2. Wetting and emulsifying properties give film-free drying after the water rinse
3. Removes tar and asphalt 10 to 15 times more effectively than ordinary petroleum distillates
4. Non-caustic, non-corrosive. Harmless to aluminum and other metals.