



632-ES
DYNA-KLEEN

SPECIALTIES FOR MAINTENANCE AND SANITATION SINCE 1947

FAST - EFFICIENT THOROUGH TWO-FISTED ACTION

CHEMICAL—Loosens tough, stubborn deposits

PHYSICAL—Flushes loosened grease, oil and dirt away from surfaces



FOR HEAVY DUTY STEAMCLEANING



FLOOR SCRUBBING IN SHOPS

**Authorized by USDA for use in
federally inspected meat and poultry plants.**

EFFICIENT AND ECONOMICAL—

Accelerates cleaning, saves labor and time. Recommended for iron, steel, copper and ferrous alloyed surfaces. Do not use on aluminum.

RECOMMENDED FOR —

- Heavy equipment and machinery shops
- Railroads
- Manufacturing Plants

Packaged in 55 gallon drums

Rev. 6-26-15

Toll Free: 800-238-5150
Local: 901-363-4340
Fax: 901-375-3600

Delta Foremost Chemical Corp.
3915 AIR PARK ST. • P.O. BOX 30310 • MEMPHIS, TENNESSEE 38130-310

Visit our Web Site at:
www.deltaforemost.com





TECHNICAL DATA

FOREMOST 632-ES DYNA-KLEEN

Technical Bulletin 632-ES-A-1

Rev. 11-28-17

- DESCRIPTION:** A highly concentrated alkaline product designed for the fast and efficient removal of heavy deposits of grease, oil and dirt from equipment and machinery. It is recommended exclusively for use on iron, steel, copper and ferrous alloyed surfaces; it will attack soft metals such as aluminum, zinc, tin, galvanized, babbitt or bearing metal. This compound cleans quickly and thoroughly by the combined chemical and physical action of penetration, saponification and detergency.
- APPLICATION:** Recommended for use in all types of pressure steam generating equipment. It is used for heavy duty cleaning of farm equipment, road machinery, industry, food processors, institutions, automotive, building maintenance and restaurants. This product is extensively used in renovating operations involving automatic and industrial equipment.
- DIRECTIONS:** **HEAVY DUTY STEAMCLEANING:** Use 1 to 3 parts per 20 parts of water. Rinse with clean water after steamcleaning.
FOR POWER SPRAY OR STEAMCLEANING: Charge solution tank with one part of concentrate to 5 to 100 parts of water depending on severity of soiling. After cleaning, rinse with water or wet steam.
MANUAL: Dilute concentrate with 5 to 40 parts water depending on severity of soiling. Apply solution to surface by spray, brush or mop. Agitate if needed, or simply rinse with clean water.
- PRECAUTIONS:** **KEEP OUT OF REACH OF CHILDREN.** Contains potassium hydroxide and ethylene glycol monobutyl ether. Causes severe burns to eyes and skin. Do not get in eyes, skin or clothing. Do not take internally. No irritation is likely following short contact periods with human skin. Prolonged and/or repeated exposure may lead to redness, swelling, and necrosis. Wash thoroughly after handling. When handling, always wear chemical splash goggles, face shield, rubber gloves and protective clothing.
FIRST AID: EYES AND SKIN: In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Wash clothing before reuse. Destroy contaminated shoes. **INGESTION:** If swallowed do not induce vomiting. If person is conscious, give large quantities of water or milk, if available. Get medical attention immediately.
Before using this product, read the Safety Data Sheet (SDS) for more detailed information regarding safe handling.